

INSTALLATION INSTRUCTIONS FOR
CEILING MOUNT NATURAL GAS
OUTDOOR INSTALLATION

This lantern must be installed by a certified plumber to conform to local codes or in absence of local codes with the national fuel gas code ANSI Z223.1.

FOR YOUR SAFETY

If you smell gas:

- 1. Shut off gas to the appliance.**
- 2. Extinguish any open flame.**
- 3. If odor continues, immediately call your gas supplier.**

FOR YOUR SAFETY

DO NOT store or use gasoline or any other flammable vapors and liquids in the vicinity of this, or any other appliance.

ATTENTION INSTALLER: Leave these instructions with the appliance so the consumer will retain them for future reference.

INSTALLATION INSTRUCTIONS

NOTE: The minimum clearance from combustible constructions is 12" top by 6" side (excluding ornamentation).

- 1) Adjust natural gas inlet pressure to 7.0 inches WC.
- 2) Install mounting pan with appropriate mounting hardware (not provided).
- 3) Reduce gas supply line from ceiling to 1/4" aluminum tubing using approved fittings only.
- 4) Make an aluminum coil using 1/4" OD aluminum tubing to allow hook-up of gas supply line to 1/4" flare male connector located in ceiling mounting box of lantern. All hook-ups must be made within the depth and height of the lantern mounting box.
- 5) Attach fixture to mounting pan with screw caps provided.